



INDUSTRIAL STEREO SCOPIC STEP MICROSCOPE ZTX-20-C2/300

FEATURES

1. Sharp stereo erect image over a wide field of view.
2. 45°inclined and 360°rotatable binocular head with locked-in eyepiece. Both ocular-tubes are with diopter adjustment $\pm 5dp$, the interpupillary distance is between 55-75mm.
3. Magnification X10, X30 (Basic)
4. Up & Down Mechanism - Pillar style. Height of pillar 300 mm
5. $\varnothing 95mm$ White/Black Working stage
6. CE approval.
7. Power supply 220V/50Hz.

Illumination:

Incident reflected halogen lamp 12V10W; transmitted halogen lamp 12V10W; Brightness is adjustable.

OPTICAL DATA

Model	Eyepiece	Objective			Auxiliary Objective			
					0.5x (optional)		0.75x(optional)	
		Magnification	Field of view (mm)	Working distance (focus distance) (mm)	Field of view (mm)	Working distance (focus distance) (mm)	Field of view (mm)	Working distance (focus distance) (mm)
ZTX-20	WF5x	5X, 15X	20, 7	80	37.5, 12.5	120	24, 8	96
	HWF10x	10X, 30X	20, 7	80	37.5, 12.5	120	25, 8	96
	WF15x	15X, 45X	15, 5	80	30, 9.5	120	18, 6	96
	WF20x	20X, 60X	10, 3.5	80	18, 6	120	12, 4	96